

PWB1200



FEATURES:

- Li-ion LFP battery module Wireless Charger
- Solar Charging Fast Charging integrated 1h 80% ٠
- Parallel Connector
- EPS Emergency power supply •

Output specifications		
Output power (Continuous)	watt	1200
Output power peak (1.5s)	watt	2400
Frequency	Hz	50
Voltage	V	230
Phases		1



Battery specifications		
Battery (Type)		Li-ion LFP
Battery rated Voltage	V	25.6
Battery design life @80% DoD	cycles	2000
Battery Nominal capacity (sizes)	W/h	1075



General Description


PWB Portable Power Station is a universal Battery Energy Storage system ideally suited to a range of applications, delivering reliable power in the most cost effective and environmentally sensitive way. Energy stored within the unit is converted electronically into AC power. Power can be stored from connection to the grid, from a generator or solar PV to ensure the most efficient, lowest maintenance and best environmental impact is achieved. Beal time monitoring is provided by on beard display to ensure achieved. Real time monitoring is provided by on board display to ensure an efficient usage.



Input specifications		
Max single-phase input	W	800
a) Charging Times @80%	h	1
b) Charging Times @100%	h	2
Max DC Solar Charging	W	400
a) DC/Solar Charging Times @80% (with 400W of solar panels and best solar lighting condition)	h	2.1
b) DC/Solar Charging Times @80% (with 200W of solar panels and best solar lighting condition)	h	4
Car lighter charging (12V DC)	Α	8
Car lighter charging time @80%	h	11



Installation data		
Length	(L) mm	376
Width	(W) mm	215
Height	(H) mm	262
Weight	kg	16
Discharing temperature range	°C	-1040
Charging temperature range	°C	040
Carton box dimension LxWxH	mm	455x295x365
Total weight (carton box included)	kg	18



Instruments, controls & connections	
Inverter protection Short Circuit	\checkmark
Inverter protection Overload	\checkmark
Inverter protection Over Temperature	
Inverter protection Low Battery	\checkmark
System status control panel	\checkmark
Battery condition	
Solar charge controller MPPT	
Parallel connector	



Output:

Schuko AC ports 230V	2
Car socket (DC 12V/10A)	1
DC 6514 (12V/5A)	2
USB-A 12 W Max (5V/2.4A)	2
USB-A Quick 24W Max (5/9/12V 3/2.2/2 A)	2
USB-C 100 W Max (5/9/12/15/20V 3/5A)	2
Wireless charger	1

99_ St 0000=

Optional features

Solar Panel PWB Power Station 20	0W
----------------------------------	----

Parallel wires PWB Power Station 12AWG (110cm)



• •

ЗАПАС

The information is aligned with the Data file at the time of download. Printed on 07/06/2024 (ID 185250)

 $\hfill \odot 2024 \mid$ PR Industrial S.r.L unipersonale – Loc. II Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc.| All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice